







# EAZY


- High bay hanging fixture.
- Polycarbonate diffuser.
- 1.50m black H05RN-F power cable, 0.20m dimmer cable and M10 suspension loop included.
- Multi-power : 100, 150 or 200W selectable via a switch at the back of the luminaire.
- Dimmable 0-10V converter built in the device.
- Can be installed at heights of up to 15m.
- Optional accessories : 270° adjustable mounting bracket, protection grid, polycarbonate reflector, microwave detector and remote control for setting the parameters of the detector(s). The microwave detector cannot be used if a 0-10V dimmer is connected to the product.
- Default microwave detector settings : hold time 10 min., daylight sensor 50 Lux, detection range 100%, stand-by dimming 30%, stand-by period continuous.





Remote control is required to configure other settings.  
This product contains 1 light source(s) of energy efficiency C.

CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen	α
HB111WW05	BLACK	CAST ALUMINIUM	AC 230V	100W	3000K	19850 Lm	15900 Lm	60°
				150W		28900 Lm	22780 Lm	
				200W		36700 Lm	29275 Lm	
HB111NW05	BLACK	CAST ALUMINIUM	AC 230V	100W	4000K	20850 Lm	16710 Lm	60°
				150W		30450 Lm	23980 Lm	
				200W		38650 Lm	30870 Lm	
HB112WW05	BLACK	CAST ALUMINIUM	AC 230V	100W	3000K	19850 Lm	16395 Lm	90°
				150W		28900 Lm	23535 Lm	
				200W		36700 Lm	30275 Lm	
HB112NW05	BLACK	CAST ALUMINIUM	AC 230V	100W	4000K	20850 Lm	17205 Lm	90°
				150W		30450 Lm	24730 Lm	
				200W		38650 Lm	31885 Lm	
HB108WW05	BLACK	CAST ALUMINIUM	AC 230V	100W	3000K	19850 Lm	15335 Lm	120°
				150W		28900 Lm	21960 Lm	
				200W		36700 Lm	30320 Lm	
HB108NW05	BLACK	CAST ALUMINIUM	AC 230V	100W	4000K	20850 Lm	16920 Lm	120°
				150W		30450 Lm	24480 Lm	
				200W		38650 Lm	32075 Lm	

ACCESSOIRES	COLOR	DESCRIPTION	
HB113		POLYCARBONATE REFLECTOR 412x151mm	
HB104	BLACK	270° ADJUSTABLE MOUNTING BRACKET	
HB110	WHITE	PROTECTION GRID	
HB114	BLACK	IP65 MICROWAVE DETECTOR	
HB115		REMOTE CONTROL FOR MW DETECTOR	

 Suspended mounting only.

 Indoor use only.

 Protected against the ingress of dust. Protected against jets of water.



Protection against an impact energy of 20 Joules.



Earth wire . Fixture equipped with primary insulation only.



Product in conformity CE.



Colour rendering index >80.



LED specifications.



Photobiological risk RG1



Test on 850°.



Power supply included.




The product is dimmable (0-10V).




5 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.