




INDY 1 A

- Spotlight for outdoor lighting.
 - Multi-power : 65, 80 or 125W selectable via a switch at the back of the luminaire.
 - Diffuser in clear tempered glass.
 - Asymmetric beam.
 - Supplied with 1.00m cable.
 - Non-dimmable converter built in the device.
- This product contains 1 light source(s) of energy efficiency E.



| CODE | COLOR | MATERIAL | AC | LED | T° (K) | LED Lumen | System Lumen |
|-----------|-------|----------------|---------|------|--------|-----------|--------------|
| FL102WW05 | BLACK | CAST ALUMINIUM | AC 230V | 65W | 3000K | 11500 Lm | 9625 Lm |
| | | | | 80W | | 13750 Lm | 11365 Lm |
| | | | | 125W | | 18750 Lm | 15525 Lm |
| FL102NW05 | BLACK | CAST ALUMINIUM | AC 230V | 65W | 4000K | 12500 Lm | 10370 Lm |
| | | | | 80W | | 14500 Lm | 12025 Lm |
| | | | | 125W | | 19500 Lm | 16275 Lm |

| ACCESSOIRES | DESCRIPTION | |
|-------------|---------------------|--|
| OU48405 | CONNECTOR 2PIN IP68 |  |
| OU48505 | CONNECTOR 3PIN IP68 |  |



Wall mounting only.



Outdoor use.



Protected against the ingress of dust. Protected against jets of water.



Protection against an impact energy of 5 Joules.



Earth wire . Fixture equipped with primary insulation only.



Vertical orientation maximum to 300°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.



Photobiological risk RG1



Test on 850°.




Power supply included.




5 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Non-replaceable control gear.



Non-replaceable light source.