### TECHNICAL DATA

## OUTDOOR


### FLOODLIGHTS



# INDY 2 A

- Spotlight for outdoor lighting.
- Multi-power : 125, 165 or 200W selectable
- via a switch at the back of the luminaire. - Diffuser in clear tempered glass.
- Asymmetric beam.
- Supplied with 1.00m cable.
- Non-dimmable converter built in the device.
- This product contains 1 light source(s) of energy efficiency E.





CODE	COLOR	MATERIAL	AC	LED	Т° (К)	LED Lumen	System Lumen
FL103WW05	BLACK	CAST ALUMINIUM	AC 230V	125W 165W 200W	3000K	20000 Lm 25500 Lm 31000 Lm	16575 Lm 21220 Lm 25695 Lm
FL103NW05	BLACK	CAST ALUMINIUM	AC 230V	125W 165W 200W	4000K	22250 Lm 27000 Lm 31000 Lm	18440 Lm 22355 Lm 25720 Lm

ACCESSOIRES	DESCRIPTION	
OU48405	CONNECTOR 2PIN IP68	
OU48505	CONNECTOR 3PIN IP68	200

	Wall mounting only.
	Outdoor use.
<b>IP</b> 65	Protected against the ingress of dust. Protected against jets of water.
<b>IK</b> 07	Protection against an impact energy of 2 Joules.
$\perp$	Earth wire . Fixture equipped with primary insulation only.
ノ 300°	Vertical orientation maximum to 300°.
CE	Product in conformity CE.
<b>CRI</b> >80	Colour rendering index >80.
LED L80B50 50.000h	LED specifications.
RG1	Photobiological risk RG1
850°	Test on 850°.
	Power supply included.
5	5 years warranty.
0	Photometric data available on our website: www.indigo-lighting.com

#### **OUTDOOR**

## FLOODLIGHTS



