




INDY 2

- Spotlight for outdoor lighting.
 - Multi-power : 125, 165 or 200W selectable via a switch at the back of the luminaire.
 - Diffuser in frosted tempered glass.
 - Supplied with 1.00m cable.
 - Non-dimmable converter built in the device.
- This product contains 1 light source(s) of energy efficiency D.



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
FL101WW05	BLACK	CAST ALUMINIUM	AC 230V	125W	3000K	22500 Lm	18785 Lm
				165W		28500 Lm	23780 Lm
				200W		33000 Lm	27385 Lm
FL101NW05	BLACK	CAST ALUMINIUM	AC 230V	125W	4000K	23500 Lm	19470 Lm
				165W		29500 Lm	24395 Lm
				200W		33750 Lm	28055 Lm

ACCESSOIRES	DESCRIPTION	
OU48405	CONNECTOR 2PIN IP68	
OU48505	CONNECTOR 3PIN IP68	



Wall mounting only.



Ground mounting only.



Outdoor use.



Protected against the ingress of dust. Protected against jets of water.



Protection against an impact energy of 2 Joules.



Earth wire . Fixture equipped with primary insulation only.



Vertical orientation maximum to 300°.



Beam 120°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.



Photobiological risk RG1





Test on 850°.




Power supply included.

5 5 years warranty.

 Photometric data available on our website: www.indigo-lighting.com

 Non-replaceable control gear.

 Non-replaceable light source.