


JACK T
















- Spotlight for accent lighting.
- Adapter for Track UNO.
- 2700K, 3000K or 4000K selectable via a switch at the back of the luminaire.
- Dimmable converter built in in the device.
- Compatible with end-of-phase dimmer.

This product contains 1 light source(s) of energy efficiency G.



| CODE | COLOR | MATERIAL | AC | LED | T° (K) | LED Lumen | System Lumen |
|---------|------------------------|-----------|---------|-----|-----------------|-----------------|----------------|
| TR42805 | MATT BLACK | ALUMINIUM | AC 230V | 10W | 2700-3000-4000K | 1120 Lm (4000K) | 770 Lm (4000K) |
| TR42813 | MATT BLACK - BRASS | ALUMINIUM | AC 230V | 10W | 2700-3000-4000K | 1120 Lm (4000K) | 770 Lm (4000K) |
| TR42806 | MATT BLACK - PINK GOLD | ALUMINIUM | AC 230V | 10W | 2700-3000-4000K | 1120 Lm (4000K) | 770 Lm (4000K) |
| TR42830 | MATT WHITE | ALUMINIUM | AC 230V | 10W | 2700-3000-4000K | 1120 Lm (4000K) | 770 Lm (4000K) |
| TR42828 | MATT WHITE - BRASS | ALUMINIUM | AC 230V | 10W | 2700-3000-4000K | 1120 Lm (4000K) | 770 Lm (4000K) |
| TR42802 | MATT WHITE - PINK GOLD | ALUMINIUM | AC 230V | 10W | 2700-3000-4000K | 1120 Lm (4000K) | 770 Lm (4000K) |



-  Ceiling mounting only.
-  Indoor use only.
-  Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.
-  Protection against an impact energy of 0,20 Joule.
-  Earth wire . Fixture equipped with primary insulation only.
-  Vertical orientation maximum to 90°.
-  Horizontal orientation maximum to 350°.
-  Beam 38°.
-  Product in conformity CE.
-  Colour rendering index >90.
-  Selectable colour temperature.
2700K
3000K
4000K
-  LED specifications.
LED
L80B10
50.000h
-  Photobiological risk RG1
-  Test on 850°.
-  Power supply included.




The product is dimmable.




5 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.