


# CADIX

- Linear structure for 48V track.

This product contains 1 light source(s) of energy efficiency G.



CODE	COLOR	MATERIAL	DC	LED	T° (K)	LED Lumen	System Lumen	L (mm)
<b>NOT DIMMABLE</b>								
TR267SW05	MATT BLACK	ALUMINIUM	DC 48V	11W	2700K	1280 Lm	777 Lm	407
TR267WW05	MATT BLACK	ALUMINIUM	DC 48V	11W	3000K	1325 Lm	783 Lm	407
TR267NW05	MATT BLACK	ALUMINIUM	DC 48V	11W	4000K	1440 Lm	992 Lm	407
TR268WW05	MATT BLACK	ALUMINIUM	DC 48V	18W	3000K	2305 Lm	1470 Lm	800
TR268NW05	MATT BLACK	ALUMINIUM	DC 48V	18W	4000K	2495 Lm	1485 Lm	800
<b>DALI DIMMABLE</b>								
TR267WW05DA	MATT BLACK	ALUMINIUM	DC 48V	11W	3000K	1325 Lm	783 Lm	407
TR267NW05DA	MATT BLACK	ALUMINIUM	DC 48V	11W	4000K	1440 Lm	992 Lm	407
TR268WW05DA	MATT BLACK	ALUMINIUM	DC 48V	18W	3000K	2305 Lm	1470 Lm	800
TR268NW05DA	MATT BLACK	ALUMINIUM	DC 48V	18W	4000K	2495 Lm	1485 Lm	800



Ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Protection against an impact energy of 0,20 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Beam 110°.



Product in conformity CE.



CRI>80



LED specifications.



Photobiological risk RG1



Test on 650°.




Connect to a constant voltage LED power supply of 48VDC.



3 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable LED light source by an electrician.