


# CAIMAN QUICK CONNECT






- Waterproof, corrosion-resistant linear luminaire.
- UV-resistant polycarbonate diffuser.
- 3000K, 4000K or 5700K selectable via a switch in the luminaire.
- Multi-power : 18 or 37W (AC4) and 28 or 56W (AC5) selectable via a switch in the luminaire.
- Non dimmable converter built in the device.
- Supplied with sliding mounting clips and hanging bracket.
- With through-wiring and quick connections without opening the luminaire.
- Optional plug-in Versabox kit : microwave sensor and remote control for setting the parameters of the detector.





This product contains 1 light source(s) of energy efficiency C.


CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen	L (mm)
AC4TWN	GREY	POLYCARBONATE	AC 230V	18W 37W	3000-4000-5700K	3225 Lm (4000K) 6450 Lm (4000K)	2775 Lm (4000K) 5550 Lm (4000K)	1200
AC5TWN	GREY	POLYCARBONATE	AC 230V	28W 56W	3000-4000-5700K	4850 Lm (4000K) 9700 Lm (4000K)	4200 Lm (4000K) 8400 Lm (4000K)	1500


ACCESSOIRES	DESCRIPTION
ACKITMWS	MICROWAVE SENSOR KIT VERSABOX 
ACREMOTEMWS	REMOTE CONTROL FOR MICROWAVE SENSOR 

 Wall and ceiling mounting only.


 Indoor and outdoor use.


 Protected against penetration of dust  
Protected against water jets.

 Protection against an impact energy of 20 Joules.


 Earth wire . Fixture equipped with primary insulation only.


 Beam 120°.


 Product in conformity CE.


 Colour rendering index >80.


 3 CCT.  
3000K  
4000K  
5700K


 LED specifications.  
L70  
100,000h

 Photobiological risk RG0


 Test on 650°.

 Power supply included.

 7 years warranty.



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.