















HUBA P



This product contains 1 light source(s) of energy efficiency E.



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
AIN3KPLBKWH	MATT BLACK - MATT WHITE	STEEL	AC 230V	15W	3000K	1600 Lm	1140 Lm
AIN3KPLBKGD	MATT BLACK - GOLD	STEEL	AC 230V	15W	3000K	1600 Lm	745 Lm
AIN3KPLWHWH	MATT WHITE	STEEL	AC 230V	15W	3000K	1600 Lm	1140 Lm
AIN3KPLWHGD	MATT WHITE - GOLD	STEEL	AC 230V	15W	3000K	1600 Lm	745 Lm



-  Suspended mounting only.
-  Indoor use only.
-  Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.
-  Earth wire . Fixture equipped with primary insulation only.
-  Beam 120°.
-  Product in conformity CE.
-  Colour rendering index >80.
-  LED specifications.
L80B20
50.000h
-  Photobiological risk RG1
-  Test on 750°.
-  Power supply included.
-  The product is dimmable.
-  5 years warranty.
-  Photometric data available on our website: www.indigo-lighting.com

-  Replaceable control gear by an electrician.
-  Replaceable LED light source by an electrician.