

# HULA P
















This product contains 2 light source(s) of energy efficiency E.





CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
SU174WW35	MATT BLACK - MATT WHITE	COMPOSITE	AC 230V	18W	3000K	1850 Lm	1000 Lm
SU174WW36	MATT BLACK - GOLD	COMPOSITE	AC 230V	18W	3000K	1850 Lm	1000 Lm
SU174WW30	MATT WHITE	COMPOSITE	AC 230V	18W	3000K	1850 Lm	1000 Lm
SU174WW80	MATT WHITE - GOLD	COMPOSITE	AC 230V	18W	3000K	1850 Lm	1000 Lm



MATT BLACK - MATT WHITE    MATT BLACK - GOLD    MATT WHITE    MATT WHITE - GOLD

-  Suspended mounting only.
-  Indoor use only.
-  Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.
-  Protection against an impact energy of 1 Joule.
-  Live parts are equipped with additional isolation protection, such as reinforced or double insulation.
-  Beam 120°.
-  Product in conformity CE.
-  Colour rendering index >80.
-  LED specifications.
-  Photobiological risk RG0
-  Test on 750°.
-  Power supply included.
-  The product is dimmable.
-  5 years warranty.
-  Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)

 Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.