


HYDRA

This product contains 1 light source(s) of energy efficiency D.



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen	α
HYB1CONEBPC	MATT BLACK - BLACK	ALUMINIUM	AC 230V	14W	2200-3000K	1920 Lm (3000K)	1150 Lm (3000K)	145°
				19W		2560 Lm (3000K)	1500 Lm (3000K)	
				24W		3200 Lm (3000K)	1800 Lm (3000K)	
HYB1CONESP	MATT BLACK - SILVER	ALUMINIUM	AC 230V	14W	2200-3000K	1920 Lm (3000K)	1500 Lm (3000K)	155°
				19W		2560 Lm (3000K)	1950 Lm (3000K)	
				24W		3200 Lm (3000K)	2400 Lm (3000K)	
HYB1OPALWPC	MATT BLACK	ALUMINIUM	AC 230V	14W	2200-3000K	1920 Lm (3000K)	1200 Lm (3000K)	
				19W		2560 Lm (3000K)	1550 Lm (3000K)	
				24W		3200 Lm (3000K)	1900 Lm (3000K)	



MATT BLACK - BLACK



MATT BLACK - SILVER



MATT BLACK

ACCESSOIRES	COLOR	MATERIAL	DESCRIPTION	L (mm)
HYBxBOLLARD	MATT BLACK	ALUMINIUM	HYDRA POST + FIXING KIT	600
HYBxSPILLKIT	MATT BLACK	ALUMINIUM	HYDRA 180° REFLECTOR	



Floor mounting only.



Outdoor use.



Protected against the ingress of dust. Protected against jets of water.



Protection against an impact energy of 20 Joules.



Earth wire . Fixture equipped with primary insulation only.



Product in conformity CE.



Colour rendering index >80.



LED specifications.



Photobiological risk RG0




Test on 650°.




Power supply included.



5 years warranty.



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.