

IRO 1

- Hanging fixture for 48V track.
- Supplied with an adjustable cable length of 1.50m.

This product contains 1 light source(s) of energy efficiency F.



CODE	COLOR	MATERIAL	DC	LED	T° (K)	LED Lumen	System Lumen
NOT DIMMABLE							
TR311SW05	MATT BLACK	ALUMINIUM	DC 48V	8W	2700K	640 Lm	465 Lm
TR311WW05	MATT BLACK	ALUMINIUM	DC 48V	8W	3000K	660 Lm	470 Lm
TR311NW05	MATT BLACK	ALUMINIUM	DC 48V	8W	4000K	690 Lm	487 Lm
DALI DIMMABLE							
TR311WW05DA	MATT BLACK	ALUMINIUM	DC 48V	8W	3000K	660 Lm	470 Lm
TR311NW05DA	MATT BLACK	ALUMINIUM	DC 48V	8W	4000K	690 Lm	487 Lm



Suspended mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Protection against an impact energy of 0,20 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Beam 50°.



Product in conformity CE.



CRI >80



LED specifications.



Photobiological risk RG1



Test on 650°.




Connect to a constant voltage LED power supply of 48VDC.



3 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable LED light source by an electrician.