



# PARO 1


- Spotlight for accent lighting for 48V track.


This product contains 1 light source(s) of energy efficiency F.





CODE	COLOR	MATERIAL	DC	LED	T° (K)	LED Lumen	System Lumen	α
<b>NOT DIMMABLE</b>								
TR286SW05	MATT BLACK	ALUMINIUM	DC 48V	8W	2700K	640 Lm	420 Lm	24°
TR286WW05	MATT BLACK	ALUMINIUM	DC 48V	8W	3000K	660 Lm	466 Lm	24°
TR286NW05	MATT BLACK	ALUMINIUM	DC 48V	8W	4000K	690 Lm	526 Lm	24°
TR285SW05	MATT BLACK	ALUMINIUM	DC 48V	8W	2700K	640 Lm	508 Lm	36°
TR285WW05	MATT BLACK	ALUMINIUM	DC 48V	8W	3000K	660 Lm	522 Lm	36°
TR285NW05	MATT BLACK	ALUMINIUM	DC 48V	8W	4000K	690 Lm	535 Lm	36°
TR284SW05	MATT BLACK	ALUMINIUM	DC 48V	8W	2700K	640 Lm	465 Lm	50°
TR284WW05	MATT BLACK	ALUMINIUM	DC 48V	8W	3000K	660 Lm	470 Lm	50°
TR284NW05	MATT BLACK	ALUMINIUM	DC 48V	8W	4000K	690 Lm	477 Lm	50°
<b>DALI DIMMABLE</b>								
TR286WW05DA	MATT BLACK	ALUMINIUM	DC 48V	8W	3000K	660 Lm	466 Lm	24°
TR286NW05DA	MATT BLACK	ALUMINIUM	DC 48V	8W	4000K	690 Lm	526 Lm	24°
TR285WW05DA	MATT BLACK	ALUMINIUM	DC 48V	8W	3000K	660 Lm	522 Lm	36°
TR285NW05DA	MATT BLACK	ALUMINIUM	DC 48V	8W	4000K	690 Lm	535 Lm	36°
TR284WW05DA	MATT BLACK	ALUMINIUM	DC 48V	8W	3000K	660 Lm	470 Lm	50°
TR284NW05DA	MATT BLACK	ALUMINIUM	DC 48V	8W	4000K	690 Lm	477 Lm	50°


 Wall and ceiling mounting only.


 Indoor use only.


 Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.

 Protection against an impact energy of 0,20 Joule.


 Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.


 Vertical orientation maximum to 85°.


 Horizontal orientation maximum to 355°.


 Product in conformity CE.

 CRI>80


 LED specifications.


 Photobiological risk RG1

 Test on 850°.

 Connect to a constant voltage LED power supply of 48VDC.

**3** 3 years warranty.

 Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)

 Replaceable LED light source by an electrician.