


RETI 2 RX

- Adjustable round semi-recessed downlight.
- Precisely defined light beam thanks to high-quality glass lens.
- Fastened with springs.
- Remote non-dimmable converter supplied.

This product contains 1 light source(s) of energy efficiency F.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO561WW05	MATT BLACK	ALUMINIUM	AC 230V	DC 450mA 36V	18W	3000K	1620 Lm	1490 Lm
DO561WW31	MATT BLACK - SATIN BRONZE	ALUMINIUM	AC 230V	DC 450mA 36V	18W	3000K	1620 Lm	1490 Lm
DO561WW30	MATT WHITE	ALUMINIUM	AC 230V	DC 450mA 36V	18W	3000K	1620 Lm	1490 Lm



MATT BLACK



MATT BLACK - SATIN BRONZE



MATT WHITE



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Protection against an impact energy of 0,20 Joule.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Hole cut to insert luminaire (95mm)



Minimum ceiling height to insert luminaire. (40mm)



Vertical orientation maximum to 90°.



Horizontal orientation maximum to 350°.



Beam 80°.



Product in conformity CE.



Colour rendering index >95.



LED specifications.



Photobiological risk RG1



Test on 650°.




Product can not be covered after installation even with insulation.





Power supply included.

450 mA Connect to a constant current Led power supply of 450mA DC.

5 5 years warranty.

 Photometric data available on our website: www.indigo-lighting.com

 Replaceable control gear by an electrician.

 Replaceable LED light source by an electrician.