


SPIRA 1 RX PLUS

- 3 in 1 adjustable round recessed downlight.
- 2700K, 3000K or 4000K as desired via a switch on the converter.
- Protective glass.
- Fastened with springs.
- Non-dimmable converter built in the device.
- Ring covering a drilling diameter of 220 to 240mm to be ordered separately.

This product contains 1 light source(s) of energy efficiency G.





CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO48805	BLACK	CAST ALUMINIUM	AC 230V	DC 950mA 36V	40W	2700-3000-4000K	3400 Lm (4000K)	2478 Lm (4000K)
DO48804	WHITE	CAST ALUMINIUM	AC 230V	DC 950mA 36V	40W	2700-3000-4000K	3400 Lm (4000K)	2478 Lm (4000K)



BLACK



WHITE

ACCESSOIRES	COLOR	MATERIAL	DESCRIPTION
DO54805	BLACK	ALUMINIUM	FINISHING RING 250mm 
DO54804	WHITE	ALUMINIUM	FINISHING RING 250mm 



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 12 mm. Protected against rain.



Protection against an impact energy of 0,50 Joule.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Hole cut to insert luminaire (175 mm)



Minimum ceiling height to insert luminaire. (200mm)



Vertical orientation maximum to 80°.



Horizontal orientation maximum to 350°.



Beam 40°.



Product in conformity CE.



Colour rendering index >90.



Selectable colour temperature.





LED specifications.



RG1 Photobiological risk RG1


850° Test on 850°.


 Product can not be covered after installation even with insulation.


 Power supply included.

950 mA Connect to a constant current Led power supply of 950mA DC.

5 5 years warranty.

 Photometric data available on our website: www.indigo-lighting.com

 Replaceable control gear by an electrician.

 Replaceable LED light source by an electrician.